Asheville Collection Specifications



Asheville Collection Specifications

	Construction: Engineered High Density Ply Core Hardwood with Tongue and Groove		Edge Profile: 1-2mm Micro Beveled Edges and Ends
	Species: French Oak		Installation: Nail, Staple, Glue, Float; Above Grade, At Grade, Below Grade
	Dimensions: 5/8″ (Nominal Overall Thickness) X 9.4" (width) X 86.6" (Varying Lengths)		Surface Treatment: 3D,advanced brush for a more pronounced grain texture
4mm	Thickness of Surface Layer: 4mm	GLOSS	Gloss: 5±2degree
	Cutting Method: Sawn		Moisture Content: 6%–9%
ABC	Grade: ABCDEF		Color Variation: Netherlands finishes Water-based Coloring

Finish:

UV/6 primer2 finish, Sherwin-Williams+overmat.

Assembling Gap: ≤0.20mm Length Deviation: ±0.5mm Width Deviation: ±0.15mm Thickness Deviation: ±0.2mm Reactive Stain: Smoke+ReactiveStain Surface Abrasion Resistance: ≥300r,S-33Sand paper Film Hardness: ≥2H Static Bending Strength: ≥30MPa Moisture Content: 6%-9%



Packaging

Area per carton: 34.10 Sqft. per Carton Weight per carton: 70.55 Lbs

Warranties: 50 year residential finish warranty. 5 year commercial warranty. Please visit www.palmettoroadfloors.com for the most current warranty information.



Environmental

Certifications: Floor Score Certified Carb II Compliant: Yes Lacy Act Compliant: Yes